



Scully Water Detector

The Portable Paste Problem Solver

Setting Standards in Safety and Dependability since 1936.



Water Detector

DESCRIPTION

The Scully WB 100G water detector is a battery operated, hand held unit. The unit is comprised of a rugged metal housing with audible alarm and a water detection sensor permanently attached via a two-conductor petroleum resistant cable. The weighted sensor is lowered into the fuel storage tank, boat bilge, truck compartment, etc. by simply unwinding the cable. The audible alarm will sound when the presence of water is detected. By lowering the weighted sensor to the bottom of the tank and raising it until the alarm shuts off, you can accurately measure the level of water within the tank. It's as easy as using a drop line and less awkward and more accurate than a messy paste covered stick. The WB 100G water detector weighs less than four pounds. The unit is self-contained and easy to store. Consult Scully for special applications.

FEATURES AND BENEFITS

- Can be used in gasoline, gasohol, diesel fuel, jet fuels and #1 through #4 fuel oil.
- Ideal for petroleum storage tanks, boat bilges and manholes.
- Available in a variety of sizes for virtually all tanks.
- No need for messy paste sticks.
- Rugged, lightweight construction.
- Inexpensive and easy to use.
- Audible alarm indicates the presence and level of water.
- Approval for use in hazardous areas.
- Battery operated.

TECHNICAL SPECIFICATIONS

Sensor Material: Non-sparking brass
Cable Jacket: PVC
Sensor Diameter: 7/8" (2.2 cm)
Housing Material: Zinc alloy, die cast
Unit Height: 6" (15.2 cm)

Power Requirements: 9 volt zinc-carbon battery
Weight: 3 lbs. (1.4 kg.)
Approvals: Factory Mutual Research and CSA for use in Class I, Division 1, Groups A, B, C & D Hazardous locations.

ORDERING INFORMATION

Description	Length	Part Number
WB 100 G	25' (7.6m)	08019

REPLACEMENT PARTS

Description	Part Number
Sensor and Cable Assembly for the WB 100G	21326
9 Volt Replacement BAttery for the WB 100 G	26903

00000 Rev A
May 2014

Copyright © 2015 Scully Signal Company. Dynacheck, Dynamic Self-Checking, Dynamic Self-Testing, Faylsafe, Golden Gallon, IntelliCheck, Intellitrol, Mark IV, Sculclamp, Sculflow, Sculmatic, Twis-Lok, Unifil, Ventafil, Ventalarm, V.I.P. and Whistler are registered trademarks of Scully Signal Company. All Rights Reserved. Specifications are subject to change without notice.



Scully Signal Company
70 Industrial Way
Wilmington, MA 01887, USA
800 272 8559 • sales@scully.com

Scully Systems Europe NV
Maanstraat 25
2800 Mechelen, Belgium
+32 (0) 15 56 00 70 • info@scully.be

Scully UK Ltd
Meridian House, Unit 33
37 Road One Winsford Industrial Estate,
Winsford Cheshire CW7 3QG, UK
+44 (0) 1606 553805 • sales@scullyuk.com

