# Standard STB



## All Husky<sup>®</sup> Safe-T-Breaks<sup>®</sup> stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

### Models 003360 and 003385

- Retains UL listing after reconnection.
- Features a pre-loaded spring and a single turn wave spring that enables valve to resist sudden pressure build-up in the hose causing nuisance separations.
- Separates at less than 200 lbf / 889.6 N which minimizes "backlash" force of separation, reducing damage to equipment.

#### Model 005230

- Retains UL listing after reconnection.
- Uses the same pre-loaded spring and a single turn wave spring as Model 003360.

 Separates at less than 115 lbf / 511.5 N.

#### Model 002273 & 002774

- Light-weight, inexpensive and disposable.
- Same instant-closing dual poppet check valve design as Model 003360.
- Separates at less than 300 lbf / 1334.4 N.

#### Model 006130

- Internal Pressure Compensating Chamber (PCC) that prevents "line shock" nuisance separations.
- Same instant-closing dual poppet check valve as Model 003360.

Model 003600

Separates at less than 225 lbf / 1000.8 N.



MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)	
003360**	¾" F x ¾" F Reconnectable Safe with scuff guard	-T-Break® 0.59 (0.26)	
005230**	<sup>3</sup> ⁄ <sub>4</sub> " F x <sup>3</sup> ⁄ <sub>4</sub> " F Reconnectable Low- Safe-T-Break <sup>®</sup> with scuff guard	Pull 0.59 (0.26)	

#### **Non-reconnectable with NPT**

MODEL NO.	DESCRIPTION	SHIPPING WEI	GHT LBS (KG)
002273	¾" F x ¾" F Non-Reconnectab	le Safe-T-Break®	0.78 (0.35)
006130**	¾" F x ¾" F PCC Non-Reconne Safe-T-Break® with scuff guard		0.52 (0.23)

#### **Reconnectable with BSPP**

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
003385**	¾" F x ¾" F Reconnectable Safe	e-T-Break®
	with scuff guard	0.57 (0.25)

#### Non-reconnectable with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)	
002774	¾" F x ¾" F Non-Reconnectable Safe-T-Break®	0.73 (0.33)	
002774A*	¾" F x ¾" F Non-Reconnectable Safe-T-Break® - Atex	0.73 (0.33)	
		**See page 2 for guard color option	


\*\*See page 2 for guard color optio

#### Construction

RECONNECTABLE SAFE-T-BREAKS®		
Body	Aluminum	
Seals	Fluorocarbon	
Springs	Stainless Steel Stainless steel load and latch spring reverse mechanism Hardened stainless steel latch ring and balls	

#### NON-RECONNECTABLE SAFE-T-BREAKS®

Body Zinc Alloys and Aluminum







**SAFE-T-BREAKS®** 



# **Standard STB**

All Husky<sup>®</sup> Safe-T-Breaks<sup>®</sup> stop the flow of fuel on both sides of the separation and have passed the demanding UL test requirements on separations without leaking or failing.

### **Dimensions and System Options**

#### **Whip Hoses**

MODEL NO.	DESCRIPTION
NPT	
002274	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose
227374	$\frac{3}{2}$ " M x $\frac{3}{2}$ " M (19 mm M x 19 mm M) Whip Hose connected to Model 002273 $\frac{3}{2}$ " F x $\frac{3}{2}$ " F Non-Reconnectable Safe-T-Break®
336074**	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose connected to Model 003360 ¾" F x ¾" F Reconnectable Safe-T-Break®
002275	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose with Swivel Nut
227375**	34'' M x $34''$ M (19 mm M x 19 mm M) Whip Hose with Swivel Nut connected to Model 002273 $34''$ F x $34''$ F Non-Reconnectable Safe-T-Break®
336075**	34'' M x $34''$ M (19 mm M x 19 mm M) Whip Hose with Swivel Nut connected to Model 003360 $34''$ F x $34''$ F Reconnectable Safe-T-Break®
BSPP	
002775	¾" M x ¾" M (19 mm M x 19 mm M) Whip Hose

#### Guards

MODEL NO.	DESCRIPTION
003096**	Scuff Guard for Model #003360, 006130 and 005230
006503**	Dispenser Scuff Guard for Model #002273 and 002774

#### **Accessories, Testing and Maintenance**

MODEL NO.	DESCRIPTION	
007000	Safe-T-Break® Drain Cup	
003813	Safe-T-Break® Demonstration Kit	

#### **Color Chart**

COLOR	SUFFIX	COLOR	SUFFIX
Blue	-01	White	-06
Red	-02	Gold	-08
Green	-03	Silver	-09
Black	-04	BP Green	-16
Yellow	-05	Pink	-20

\*\*Safe-T-Breaks® and Safe-T-Break® Scuff Guards are to be ordered with the corresponding guard color option added to the model number.

Example: If BLUE guards are desired, add guard color option -01 to the model number (004034-01).

For custom colors, a minimum order of 4,000 guards will be required.

Model 003360



#### Model 006130



#### Model 002273





2325 Husky Way • Pacific, MO 63069 (800) 325-3558 • Fax (636) 825-7300 www.husky.com • sales@husky.com