

40' MAXIMUM HOSE CAPACITY

FLUIDS HANDLED


- Air.
- Water.
- Antifreeze Solutions.
- Synthetic and Mineral Oils.
- Grease.

MARKETS / APPLICATIONS

- Car and truck dealers.
- Service shops.
- General manufacturing.
- Service stations.
- Quick lubes.

MOUNTING

- Floor.
- Wall.
- Ceiling.
- Tank.



Full metal hose reels, can handle up to 40' x 1/2" hose.



04
HOSE REELS

HOSE REEL PART No.	HOSE LENGTH	HOSE I.D.	OUTLET THREAD	MAX. WORKING PRESSURE	NET WEIGHT	REEL ONLY WITH SWIVEL PART No.
LOW PRESSURE - AIR, WATER						
1411	30'	3/8"	3/8" NPTM	300 psi	41 lb	1402
1413	40'	3/8"	3/8" NPTM	300 psi	43 lb	1402
1414*	30'	3/8"	1/4" NPTM	300 psi	41 lb	1402
1416*	40'	3/8"	1/4" NPTM	300 psi	43 lb	1402
1417	40'	1/2"	1/2" NPTM	300 psi	46 lb	1402
MEDIUM PRESSURE OILS, FLUIDS						
1424	30'	3/8"	3/8" NPTM	2,000 psi	42 lb	1402
1425	40'	3/8"	3/8" NPTM	2,000 psi	45 lb	1402
1428	30'	1/2"	1/2" NPTM	2,000 psi	45 lb	1402
1426	40'	1/2"	1/2" NPTM	2,000 psi	48 lb	1402
HIGH PRESSURE GREASE						
1432	30'	1/4"	1/4" NPTM	5,000 psi	45 lb	1403
1435	50'	1/4"	1/4" NPTM	4,000 psi	48 lb	1403

- Fatigue resistant steel spring for years of durable performance and even load when pulling and recoiling the hose.
- Full metal double pedestal arm construction, epoxy powder coated for increased wear resistance.
- Forged brass shaft ensures a leak free operation.
- Hose reels with hose include 30" inlet hose.



Hose reels are delivered in ceiling mount position.

* Special reels with 3/8" hose and 1/4" NPT end.

Reel includes inlet swivel.

Reel with hose includes hose stop and 30" inlet hose. 40' models for ceiling mount use only.

MANUAL FOR ALL 1400 SERIES HOSE REELS: 850 804