NATIONAL-SPENCER, INC.

ZEE LINE LUBRICATION EQUIPMENT


Phone 800-231-1525 Fax 800-637-9511 Web Address www.zeeline.com




Part # 1730R

Air Operated Stub Style Double Action 5:1 Oil Pump

For dispensing fluid from various sized containers by adjusting the length of suction tube to fit





Features

- Delivery rate 4.7 GPM
- Accommodates various tank depths by adding personalized suct
- ❖ 5:1 ratio stub style
- Air regulator with gauge, filter and automatic water drain 1559A-ASSY
- Thread size 1" NPT
- Maximum fluid viscosity 240 SAE
- ❖ Air consumpion 8.82 CFM
- Foot valve and screen
- ❖ ½" x 48" oil hose
- ❖ ¼" x 48" air hose
- Ball valve
- Quick connect couplers for air
- Bung adapter

Recommended for

- ✓ Oil
- ✓ Antifreeze

Application

Situations where personalized tube length enhances flexibility of system

Number of boxes and contents

- □ 1 box (29" x 6" x 6") (17 lb.)
- UPC code 0 1595441696 8

To personalize the pump, take a 1" diameter water pipe, thread it and screw between the pump and the foot valve using chemical sealant to prevent air from entering during pumping, or to prevent fluid leaking out when not in use.

Foot valve (included) is essential for neutralizing the effect caused by the suction distance. Prevents emptying of the suction tube during idle periods so that the pump is always ready for use