



Model 305, 305XP & 305XPA Cap and Adaptor

SPECIFICATION SHEET

Application

Tank monitor caps and adaptors are installed on tank monitor riser pipes to keep water and debris out while providing a liquid tight opening for the probe wire to pass through.

Features and Details

- Keeps water, dirt, and debris out of the tank
- Lockable with a padlock
- Prevents vapors from escaping
- Low profile models when space is limited
- Easy to engage push-on
- Large easy-to-grip pull ring makes it fast and easy to remove
- **305SA** has a top section that rotates with the movement of the delivery hose while the bottom section remains securely in place

Materials of Construction

- Body (adaptor)... brass
- Body (cap)... aluminum
- Cam levers... aluminum (4"), brass (2")
- Gaskets... Buna-N (Viton® optional for 305XP)
- Cable connector... plastic

305SA

- O-ring... Teflon® encapsulated Viton®
- Set screws... stainless steel

305XPV


- Vent tube... copper

Certifications and Listings

Some models are CARB Certified, VR-102; Some models VR-402, CARB VR-102 (XPA series)



305 (2")



305XP (2")



305 (4")



305XP (4")



305SA (4")



305XPV (4")

Product numbers and more information on next page...



MORRISON BROS. CO.



Model 305, 305XP & 305XPA Cap and Adaptor (continued)

	Item Number	A	B	C	D	E	F	Weight
	305---0000 AA	2"	BR	No	NA	NA	B	1.50
EVR	305---0000AAEVR	2"	BR	Yes	NA	NA	B	1.50
	305---0200 AA	4"	BR	No	NA	NA	B	2.40
EVR	305---0200AAEVR	4"	BR	Yes	NA	NA	B	2.40
	305SA-0200 AA	4"	BR	No	NA	NA	B	5.50
	305XP-2100 AC	2"		No	3/8"	NA	B	0.75
	305XP-2200 AC	2"		No	3/8"	3/8"	B	0.75
EVR	305XP-2200ACEVR	2"		Yes	3/8"	3/8"	B	0.75
	305XP-2300 AC	2"		No	1/2"	NA	B	0.75
	305XP-2400 AC	2"		No	1/2"	1/2"	B	0.75
EVR	305XP-2400ACEVR	2"		Yes	1/2"	1/2"	B	0.75
	305XP-0100 AC	4"		No	3/8"	NA	B	2.0
EVR	305XP-0100ACEVR	4"		Yes	3/8"	NA	B	2.0
	305XP-0200 AC	4"		No	3/8"	3/8"	B	2.0
EVR	305XP-0200ACEVR	4"		Yes	3/8"	3/8"	B	2.0
	305XP-1100 AC	4"		No	1/2"	NA	B	2.0
EVR	305XP-1100ACEVR	4"		Yes	1/2"	NA	B	2.0
	305XP-1200 AC	4"		No	1/2"	1/2"	B	2.0
EVR	305XP-1200ACEVR	4"		Yes	1/2"	1/2"	B	2.0
	305XP-4100 AC	4"		No	3/8"	NA	V	2.0
	305XP-4200 AC	4"		No	3/8"	3/8"	V	2.0
	305XP-5100 AC	4"		No	1/2"	NA	V	2.0
	305XP-5200 AC	4"		No	1/2"	1/2"	V	2.0

	Item Number	A	B	C	D	E	F	Weight
	305XPA2100 AK	2"	BR	No	3/8"	NA	B	2.50
	305XPA2200 AK	2"	BR	No	3/8"	3/8"	B	2.50
EVR	305XPA2200AKEVR	2"	BR	Yes	3/8"	3/8"	B	2.50
	305XPA2300 AK	2"	BR	No	1/2"	NA	B	2.60
	305XPA2400 AK	2"	BR	No	1/2"	1/2"	B	2.60
EVR	305XPA2400AKEVR	2"	BR	Yes	1/2"	1/2"	B	2.60
	305XPA0100 AK	4"	BR	No	3/8"	NA	B	5.0
EVR	305XPA0100AKEVR	4"	BR	Yes	3/8"	NA	B	5.0
	305XPA0200 AK	4"	BR	No	3/8"	3/8"	B	5.0
EVR	305XPA0200AKEVR	4"	BR	Yes	3/8"	3/8"	B	5.0
	305XPA1100 AK	4"	BR	No	1/2"	NA	B	5.0
EVR	305XPA1100AKEVR	4"	BR	Yes	1/2"	NA	B	5.0
	305XPA1200 AK	4"	BR	No	1/2"	1/2"	B	5.0
EVR	305XPA1200AKEVR	4"	BR	Yes	1/2"	1/2"	B	5.0
	305XPV0100 AC	4"		No	(2) 3/8"	NA	B	2.75
	305XPV0100 AK	4"		No	(2) 3/8"	2 x 3/8"	B	2.75

SPECIFICATION OPTIONS:

A—Size (inches)
B—Adaptor if included, brass (BR)
C—EVR approved: Yes or no
D—Threaded port hole: 3/8", 1/2" or NA
E—Cable connector: 3/8", 1/2" or NA
F—Cap gasket: Buna (B), Viton®(V)
Weight—Shipping weight (lbs)

570 E. 7th Street, P.O. Box 238 | Dubuque, IA 52004-0238

t. 563.583.5701 | 800.553.4840 | f. 563.583.5028



MORRISON BROS. CO.

www.morbros.com