## **Application**

End-of-Line flame arresters are designed to be installed at the end connection of a tank vent line. The flame arrester provides a protection barrier that deters a flame generated from a source outside of the tank from flashing through the vent into the vapor space of the tank.

## **Features and Details**

- 304 stainless arrester plates provide long term corrosion resistance and durability
- Easy access for visual inspection and periodic maintenance
- Full 2" and 3" NPT vent line air flow capacity
- Water-resistant cover sheds water away from the vent line

## **Materials of Construction**

- · Base.... 356 tempered aluminum
- Cover... Aluminum
- Arrester plates... 304 stainless steel
- Threaded hardware... 18-8 stainless steel

## **Code Compliance**

cULus 525-Standard for Flame Arresters-Edition 8

Item Number	Size	Venting Capacity (@2.5 PSI)	Diameter	Overall Height	Weight (lbs)	List Price
3520200 AA	2"	90,000 SCFH	6¾"	5½"	7.87	\$356
3520300 AA	3"	184,000 SCFH	8"	8"	15.60	\$716



Note: For petroleum storage tanks containing Group D\* fluids.

\*NFPA 70, the National Electrical Code, lists or defines hazardous gases, vapors, and dusts by "Groups." Consult these resources for information on Group D fluids.