

50' MAXIMUM HOSE CAPACITY

### FLUIDS HANDLED


- Air.
- Water.
- Antifreeze and Windshield Wash Solutions.
- High Pressure Hot Water.
- Synthetic and Mineral Oils.
- DEF / AdBlue®
- Grease.

### MARKETS / APPLICATIONS

- Car and truck dealers.
- Service shops.
- Fleets.
- General manufacturing.
- Service stations.
- Lube trucks.
- Quick lubes.

### MOUNTING

- Floor.
- Wall.
- Ceiling.
- Tank.



Aluminum base and arms with composite spool hose reels, can handle up to 50' x 1/2" hose.



HOSE REEL PART No.	HOSE LENGTH	HOSE I.D.	OUTLET THREAD	MAX. WORKING PRESSURE	NET WEIGHT	REEL ONLY WITH SWIVEL PART No.
<b>LOW PRESSURE - AIR, WATER</b>						
<b>506 101</b>	30'	3/8"	3/8" NPTM	300 psi	26.71 lb	<b>506 910</b>
<b>506 121</b>	50'	3/8"	3/8" NPTM	300 psi	31.3 lb	<b>506 912</b>
<b>506 122</b>	50'	1/2"	1/2" NPTM	300 psi	32.8 lb	<b>506 914</b>
<b>LOW PRESSURE DEF (AISI 316 STAINLESS STEEL AND ACETAL FLUID PATH)</b>						
<b>506 702</b>	30'	1/2"	1/2" BSPPM	300 psi	28.7 lb	<b>506 976</b>
<b>506 722</b>	50'	1/2"	1/2" BSPPM	300 psi	34.1 lb	<b>506 978</b>
<b>MEDIUM PRESSURE OILS, FLUIDS</b>						
<b>506 202</b>	30'	1/2"	1/2" NPTM	2,000 psi	27.8 lb	<b>506 920</b>
<b>506 222</b>	50'	1/2"	1/2" NPTM	2,000 psi	32.8 lb	<b>506 922</b>
<b>HIGH PRESSURE WATER UP TO 200 °F</b>						
<b>506 421</b>	50'	3/8"	3/8" NPTM	2,400 psi	33.3 lb	<b>506 942</b>
<b>HIGH PRESSURE GREASE</b>						
<b>506 300</b>	30'	1/4"	1/4" NPTM	5,000 psi	27.3 lb	<b>506 930</b>
<b>506 321</b>	50'	3/8"	1/4" NPTM	4,000 psi	35.3 lb	<b>506 936</b>
<b>WASTE OIL SUCTION</b>						
<b>506 503</b>	20'	5/8"	1/2" NPTM	2,000 psi	29.3 lb	<b>506 950</b>

- Aluminum base and guide arm provide the rigidity to withstand the most demanding applications while offering a reduced weight for easy installation.
- Fatigue resistant steel spring for years of durable performance and even load when pulling and recoiling the hose.
- Fully ported shaft and swivel.
- Spool mounted on two permanently lubricated and sealed ball bearings to reduce torque load on spring for smooth retraction and longer life.
- Large guide latching area for easier operation.
- Six roller guide outlet prevents hose pinching and reduces friction.
- Hose guide arm can be placed in different positions to accommodate any method of mounting.
- Hose reels with hose include 30" inlet hose.



Hose reels are delivered in ceiling mount position.

MANUAL FOR ALL 506 SERIES HOSE REELS: 850 819