

Dixon® Type D Couplers
coupler x female NPT

Features:

- Couplers are supplied standard with a Buna-N gasket. Other gasket types are available on pages 167 - 170.
- ½" Dixon® coupler has only one cam arm.
- Pull rings are not supplied on ½" - 1" Dixon® couplings.

Size	356T6 Aluminum Part #	Aluminum Hard Coat Part #	Brass Part #
½"	50-D-AL	---	50-D-BR
¾"	75-D-AL	---	75-D-BR
1"	100-D-AL	---	100-D-BR
1¼"	125-D-AL	---	125-D-BR
1½"	150-D-AL	150-D-ALH	150-D-BR
2"	200-D-AL	200-D-ALH	200-D-BR
2½"	250-D-AL	---	250-D-BR
3"	300-D-AL	300-D-ALH	300-D-BR
4"	400-D-AL	400-D-ALH	400-D-BR
5"	500-D-AL	---	500-D-BR
6"	600-D-AL	600-D-ALH	600-D-BR
8"	800-D-AL ^{1,2}	---	---

¹ Dixon® and Boss-Lock™ cam & groove couplings *do not interchange in the 8" size.*

² The 8" Dixon® design has 4 cam arms.



356T6 aluminum



aluminum hard coat



brass



unplated malleable iron



316 stainless steel

Size	Unplated Malleable Iron Part #	316 Stainless Steel Part #
½"	---	50-D-SS
¾"	---	75-D-SS
1"	---	100-D-SS
1¼"	---	125-D-SS
1½"	150-D-MI	150-D-SS
2"	200-D-MI	200-D-SS
2½"	---	250-D-SS
3"	300-D-MI	300-D-SS
4"	400-D-MI ¹	400-D-SS
5"	500-D-MI	500-D-SS
6"	---	600-D-SS

¹ ductile iron