

(803)748-1000

sales@performance-ink.com



PERFORMANCE INK,

INCORPORATED



FUEL FILTERS

Options Available For Particulate Removal,
Water Detection, & Phase Separation

(803)748-1000

sales@performance-ink.com



PERFORMANCE INK,

INCORPORATED

REMOVE PARTICULATE & DETECT
WATER OR PHASE SEPARATION
MULTI-FUEL MEDIA

Part # 2104-446



400MB-10

1 1/2"-16 THREAD // 1" FLOW
MAX FLOW: 25 GPM / 94.6 LPM
MAX PRESSURE: 50 PSI / 3.4 BAR
MAX DIFF. PRESSURE: 25 PSID / 1.7 BAR DIFF.

REMOVE PARTICULATE
CELLULOSE MEDIA

Part # 2104-447



400-30

1 1/2"-16 THREAD // 1" FLOW
MAX FLOW: 25 GPM / 94.6 LPM
MAX PRESSURE: 50 PSI / 3.4 BAR
MAX DIFF. PRESSURE: 25 PSID / 1.7 BAR DIFF.

REMOVE PARTICULATE &
DETECT WATER
HYDROSORB MEDIA

Part # 2104-448



400HS-30

1 1/2"-16 THREAD // 1" FLOW
MAX FLOW: 25 GPM / 94.6 LPM
MAX PRESSURE: 50 PSI / 3.4 BAR
MAX DIFF. PRESSURE: 25 PSID / 1.7 BAR DIFF.

REMOVE PARTICULATE
CELLULOSE MEDIA

Part # 2104-449



400-10

1 1/2"-16 THREAD // 1" FLOW
MAX FLOW: 25 GPM / 94.6 LPM
MAX PRESSURE: 50 PSI / 3.4 BAR
MAX DIFF. PRESSURE: 25 PSID / 1.7 BAR DIFF.

REMOVE PARTICULATE
CELLULOSE MEDIA

Part # 2104-450



300-30

1"-12 THREAD // 1" FLOW
MAX FLOW: 25 GPM / 94.6 LPM
MAX PRESSURE: 50 PSI / 3.4 BAR
MAX DIFF. PRESSURE: 25 PSID / 1.7 BAR DIFF.

REMOVE PARTICULATE & DETECT
WATER OR PHASE SEPARATION
MULTI-FUEL MEDIA

Part # 2104-451



400MB-30

1 1/2"-16 THREAD // 1" FLOW
MAX FLOW: 25 GPM / 94.6 LPM
MAX PRESSURE: 50 PSI / 3.4 BAR
MAX DIFF. PRESSURE: 25 PSID / 1.7 BAR DIFF.

REMOVE PARTICULATE & DETECT
WATER OR PHASE SEPARATION
MULTI-FUEL MEDIA

Part # 2104-536



300MB-10

1"-12 THREAD // 1" FLOW
MAX FLOW: 25 GPM / 94.6 LPM
MAX PRESSURE: 50 PSI / 3.4 BAR
MAX DIFF. PRESSURE: 25 PSID / 1.7 BAR DIFF.

REMOVE PARTICULATE &
DETECT WATER
HYDROSORB MEDIA

Part # 2104-537



400HS-10

1 1/2"-16 THREAD // 1" FLOW
MAX FLOW: 25 GPM / 94.6 LPM
MAX PRESSURE: 50 PSI / 3.4 BAR
MAX DIFF. PRESSURE: 25 PSID / 1.7 BAR DIFF.