

# PRO20-115

Impressive 20 GPM flowrate is ideal for fleet, agriculture or industrial applications with stationary storage tanks.



**FOR USE WITH** gasoline, diesel fuel and kerosene.  
Refer to Owner's Manual for full list of fuels.

- Extended duty cycle tested to exceed industry standards
- Center based inlet includes pressure relief and easy fuel strainer access
- Field replaceable switch and vanes
- Tank adapter included
- Thermally protected motor
- Vacuum breaker ready, see Accessories for kit (page 10)
- Extreme Temperature Series (XTS) model available

## PRO20-115 SPECIFICATIONS

Flow Rate	20 GPM (76 L/min)
Voltage	115V (ac)
Type	Carbon Vane
Duty Cycle (On / Off)	30 min. / 30 min.
Inlet / Outlet Size	1 in. / 1 in. NPT
Dispensing Hose	18 ft. (5.5 m) x 1 in.
Nozzle Holder	Lockable
Warranty	4 Year

## ORDERING INFORMATION

Model	Part No.	Nozzle	Hose	Temperature Rating
PRO20-115AD	503000-03	Automatic Diesel	18 ft.	-20° F / -29° C
PRO20-115MD	503000-02	Manual Diesel	18 ft.	-20° F / -29° C
PRO20-115PO	503000-01	None	None	-20° F / -29° C

## Extreme Temperature Series (XTS)

PRO20-115PO/XTS	503000-05	None	None	Tested to -40° F / -40° C
-----------------	-----------	------	------	---------------------------

