

Highlights (2" & 4" Floats)

- Designed for applications involving 2", 3" or 4" riser pipes.
- Each float set contains a product and water float.
- Compatible with a wide variety of petroleum products.
- Water floats are colored red for gasoline and blue for diesel assure compatibility with most liquids.

Highlights (Chemical Floats)

- Suitable for use in a wide variety of chemical applications, consult factory for chemical compatibility issues.
- Use one float per TSP-LL2-I probe.
- Float specific gravity 0.55 to 0.63.
- Collapse pressure 500 psi/g minimum.

Highlights (LPG Floats)

- Designed for applications involving tank openings of at least 2".
- Single float used for monitoring the level of LPG (propane) fuel.
- Suitable for monitoring pressurized products.
- For use in USTs or ASTs with TSP-LL2 or TSP-LL2-I probes. TSP-LPG/EU float can be used with locally supplied tank isolation sleeves.

Float Kits

A variety of inventory control and leak detection float kits for various applications.



Ordering Information

Model	Description
TSP-IDF2	2" float set for diesel tanks
TSP-IGF2	2" float set for gasoline tanks
TSP-IDF4	4" float set for diesel tanks
TSP-IGF4	4" float set for gasoline tanks
TSP-LPGF	2" float for LPG tanks, with or without isolation sleeve
TSP-SSP	2-1/16" OD, #316 stainless steel float for chemical applications only

Note: Order one float set for each LL2 Mag probe.

Specifications

- 2" and 4" float materials: Constructed of nitrile rubber and PVDF. Water floats contain either stainless steel or nickel plated brass ballast.
- TSP chemical float materials: #316 stainless steel product float with 2-1/16" OD.