

PRO25-012

When reduced fueling time is critical, the high-flow PRO25 delivers with up to 25 GPM.

25 GPM
12 VOLT



4 YEAR
PUMP
WARRANTY



- Extended duty cycle tested to exceed industry standards
- Weight centering inlet base includes pressure relief and easy fuel strainer access
- Field replaceable switch and vanes
- 40 amp circuit breaker motor protection
- Extreme Temperature Series (XTS) model available
- Factory-installed power cord

PRO25-012 SPECIFICATIONS

Flow Rate	25 GPM (95 L/min)
Voltage	12V (dc)
Type	Carbon Vane
Duty Cycle (On / Off)	30 min. / 30 min.
Power Cord	18 ft. (5.5 m) x 10/2 AWG
Inlet / Outlet Size	1 in. / 1 in. NPT
Dispensing Hose	18 ft. (5.5 m) x 1 in.
Suction Pipe	Metal, 1 in. NPT, adjustable to 40 in. (101.6 cm)
Nozzle Holder	Lockable
Warranty	4 Year

ORDERING INFORMATION

Model	Part No.	Nozzle	Hose	Suction Pipe	Temperature Rating
PRO25-012AD	502000-03	Automatic Diesel	18 ft.	Metal	-20° F / -29° C
PRO25-012MD	502000-02	Manual Diesel	18 ft.	Metal	-20° F / -29° C
PRO25-012PO	502000-01	None	None	None	-20° F / -29° C

Extreme Temperature Series (XTS)

PRO25-012PO/XTS	502000-05	None	None	None	Tested to -40° F / -40° C
-----------------	-----------	------	------	------	---------------------------

FOR USE WITH gasoline, diesel fuel and kerosene. Refer to Owner's Manual for full list of fuels.

