

OPW Pulsers



Model 500 Pulser

- ◆ Counts one penny per pulse on a 101, 2002E, VR-10, and VR10/4 or 1/10 gallon or 1/100 gallon per pulse on any VR computing or non-computing register
- ◆ Main shaft and shaft extensions are machined from solid aluminum
- ◆ Intrinsically safe
- ◆ No conduit required between barrier and pulser head
- ◆ Will pulse any voltage 5 to 170 volts AC or DC
- ◆ Compatible with most self-service readout equipment, card and key systems
- ◆ Jumpers used to set pulser for type of pump computer being used
- ◆ Available in 12 VDC, 120 VAC, and 220 VAC pumps/dispensers. Part No. 4500211



Model 800-F Pulser

- ◆ Counts 1/10 gallon per pulse and is designed to work with the Fillrite 800 or 900 series registers
- ◆ No conduit required between barrier and optical head
- ◆ Will pulse any voltage 5 to 170 volts AC or DC
- ◆ Compatible with most self-service readout equipment, card and key systems
- ◆ Available in 12 VDC, 120 VAC and 220 VAC

Contact your local OPW representative to learn more about OPW's complete family of Pulsers today!

Phone: (708) 485-4200 ◆ Fax: (708) 485-4630 ◆ 6900 Santa Fe Drive ◆ Hodgkins, Illinois USA 60525 ◆ www.opwglobal.com

Ordering Specifications

PULSERS	Model	500	800-F
	Part Number	4000500	4000800-F
	Pulse Ratio	\$.01/1/10,1/100	1/10
	Computing Device		
	101	• / •	
	2001/2002	/ •	
	2002E	• / •	
	VR10/4	• / •	
	VR10	• / •	
	Non-computer	•	
	Fill-Rite 800/900		•
	Tokheim/Gasboy 793/50		
	Veeder-Root 7886/7887		
	Gilbarco Highline 111B/MPD		